

TL SM105-SA



- High precision tweezers for placing SOT packages vertically

| | | | | | |
|--------------|------------|---|-----------|-------------|-------|
| | 731415 | | | L mm | g |
| TL SM 105-SA | 0110797 | 1 | SM 105-SA | 120 | 15 |

TL SM107-SA



- High precision tweezers for positioning all flat devices at 60° angle
- Material: stainless steel

| | | | | | |
|--------------|------------|---|-----------|-------------|-------|
| | 731415 | | | L mm | g |
| TL SM 107-SA | 0110810 | 1 | SM 107-SA | 120 | 15 |

TL SM108-SA



- High precision tweezers for positioning and soldering 1 mm wide components. Tips are grooved inside
- Material: stainless steel, anti-magnetic, anti-acid
- Tips grooved inside

| | | | | | |
|--------------|------------|---|-----------|-------------|-------|
| | 731415 | | | L mm | g |
| TL SM 108-SA | 0110827 | 1 | SM 108-SA | 120 | 15 |

TL SM109-SA



- High precision tweezers for positioning and soldering 1 mm wide components. Tips are grooved inside
- Material: stainless steel, anti-magnetic, anti-acid
- Tips 45° angle and grooved inside

| | | | | | |
|--------------|------------|---|-----------|-------------|-------|
| | 731415 | | | L mm | g |
| TL SM 109-SA | 0110834 | 1 | SM 109-SA | 120 | 15 |

TL SM110-SA



- High precision tweezers with grooved tips for positioning monolithic chip capacitors
- Material: stainless steel, anti-magnetic, anti-acid

| | | | | | |
|--------------|------------|---|-----------|-------------|-------|
| | 731415 | | | L mm | g |
| TL SM 110-SA | 0110841 | 1 | SM 110-SA | 120 | 15 |

TL SM111-SA



- High precision tweezers for positioning 5 mm monolithic chip capacitors with flat base
- Material: stainless steel, anti-magnetic, anti-acid
- Grooved tips 2 mm long

| | | | | | |
|--------------|------------|---|-----------|-------------|-------|
| | 731415 | | | L mm | g |
| TL SM 111-SA | 0110858 | 1 | SM 111-SA | 120 | 15 |