

Top Gun™

Ionizing Air Gun

SIMCO's Top Gun is a high performance ionizing air gun designed for electronics and cleanroom applications. Balanced to $0 \pm 15V$, the Top Gun features high blow-off force to provide efficient cleaning and rapid static charge decay. A filter at the exit of the gun ensures that the air is clean.

The gun body is lightweight but durable. It features a light touch trigger, making it comfortable even for extended use. All functionality is built into the gun, including a flow control valve, a balance adjustment for calibration, and a two-level LED which indicates both power and ionization. The gun and cable are static dissipative. A hanger is provided for easy mounting.

- ▶ *Filter at the exit of the gun ensures that the air is clean*
- ▶ *Lightweight gun with ergonomic design for user comfort*
- ▶ *Flow control valve adjusts airflow for the specific application*
- ▶ *Electrical activation of ionization and airflow extend effectiveness of emitter with no maintenance*

- ▶ *Ionization indicator light verifies that ionization is present*
- ▶ *Electronically balanced ion output to $0 \pm 15V$ protects ESD-sensitive components and assemblies*

Top Gun™ Ionizing Air Gun



Typical applications include:

- Electronic Assembly
- Medical Device Manufacturing and packaging
- Semiconductor and Flat Panel Display Processes



An Illinois Tool Works Company
Ionization for Electronics Manufacture

Specifications:

System Performance

Discharge Time: 1.3 Seconds at 6" amd 3- psi (1000V to 100V); 0.5 seconds at 2" and 60 psi (1000V to 100V)

Specifications

Unit Part Number:	4005105	4006599	4005106	4006600
Cable Length:	7' (2.13 m)	14' (4.26 m)	7' (2.13 m)	14' (4.26 m)
Line Voltage:	120 VAC	120 VAC	230 VAC	230 VAC
Frequency:	0/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Line Current (at rest):	0.01 Amps	0.01 Amps	0.005 Amps	0.005 Amps
Line Current (operation):	0.10 Amps	0.10 Amps	0.05 Amps	0.05 Amps

Power Inlet: IEC320

Air Inlet: 1/8 NPT (female)

Input Pressure: 100 PSI (7 bar) maximum, clean dry air or nitrogen

Air Consumption: 2.4 SCFM at 30 PSI
(68 l/min. at 2 bar)
4.6 SCFM at 60 PSI
(130 l/min. at 4 bar)
7.4 SCFM at 100 PSI
(210 l/min. at 7 bar)

Output Pressure: Pressure relief in nozzle, complies with OSHA requirements.

Replaceable Filter: 0.01 micron

Noise Level: 76 dB at 30 PSI (2 bar)
89 dB at 60 PSI (4 bar)
97 dB at 100 PSI (7 bar)

Measured 24" (600 mm) from nozzle.

Operating Temperature: 32°F (0°C) to 104°F (40°C)

Construction: Gun: static dissipative polycarbonate / ABS alloy
Cable: static dissipative polyurethane

Weight: Gun: 6.5 ounces (185 g)
Cable: 1.25 ounces / ft (115 g / m)

Power Unit Size: 6.45" H x 5.20" W x 3.35" D
(not including flanges) (164 mm H x 132 mm W x 85 mm D)

In Ionization technology, SIMCO® clearly has the leadership role. Our research and manufacturing facilities are worldwide...our technical expertise is second to none...and our products simply inspire the competition. For a no-hassle assessment and quote call 800-538-0750 (in USA). Or log on to www.simco.biz.


An Illinois Tool Works Company
Ionization for Electronics Manufacture

SIMCO®

Ionization for Electronics Manufacture

2257 North Penn Road
Hatfield PA 19440 USA
In USA: 800-538-0740
Tel: 215-997-0590
Fax: 215-997-3450
Web: www.simco.biz
email: info@esimco.com

Your Local Representative



Products manufactured by SIMCO under USA and International patent(s).
Specifications subject to change without notice. August 2004 Copyright © 2004 SIMCO
5200892 - Printed in USA