HOT MARKER®

# SP8600

AUTOMATIC MARKING MACHINE FOR TUBE, MARKER LABEL & TERMINAL ID BOARD



### **HOT MARKER**® **SP8600** Thermal transfer printer for cable and wire identifications

## Industries served


Our Hotmarkers have been widely used for cable identifications across many manufacturing industries including:

Control panels / Switchgear Wire harnesses Industrial installations Heavy electrical machinery Aircraft / Shipbuilding Railway vehicle / Automobile

## Key features

You can produce different kinds of cable marker sleeves effectively, as you need. SP8600 can automatically mark and cut various types of tubes. Marking speed increased by about 10% (as compared with previous model SP6600)

Applicable tube size: Outside Diameter: 2.0~28.0 mm Laid-flat width: 3.2~45.0 mm





# **PC-link function**

Bundled software "CTKPCMS" enables you to:

- Handle marking data efficiently with on-screen previews and error windows.
- Utilize Windows' TrueType fonts for marking native characters, etc.
- Print Code 39 barcodes.
- Transfer marking data to SP8600 with a USB flash drive.



# **Stand-alone use**

**Optional keyboard allows stand-alone operation** through menu screen on the LCD.



\*Keyboard is available at extra cost.

## **SP8600 MAIN SPECIFICATIONS**

#### MAIN UNIT

MARKING SYSTEM			Thermal head type		
MODEL OF TH	HERI	MAL HEAD	ТРН933		
	PVC tubes		0.D. 2.0 mm through 28.0 mm		
	Heat shrink tubes		Laid-flat width up to 45 mm (approx.)		
APPLICATIONS	Ma	arker Labels	Precut type (PVCW0617, etc.)		
APPLICATIONS	Marker Labeis		Long type (PETS0699, etc.)		
	terminal ID boards		"HOTMARKER" brand of Marker Plates of various sizes		
FONT STYLE			CTK original fonts		
			2.4 x 2.4mm (HOR/VER) 1.8 x 1.8mm (HOR/VER)		
	C⊢	ARACTER SIZE	2.4 x 1.2mm (HOR/VER) 1.8 x 0.9mm (HOR/VER)		
	AND ORIENTATION		3.0 x 2.4mm (HOR/VER) 2.0 x 1.2mm (HOR/VER)		
STANDARD			5.0 x 3.0mm (HOR) 2.7 x 1.2mm (HOR)		
FONTS	CHARACTERS INCLUDED*1		Numerals 0 - 9 Modern alphabet letters Capital: A - Z Lowercase: a - z Signs + - /. etc.		
	1	CHARACTER SIZE	2.4 x 2.4mm (HOR) 3.0 x 2.4mm (HOR)		
SPECIAL	1	KIND OF CHARACTERS	<u>69</u> ⊕⊕±+ _(underscore) preinstalled		
FONTS	2	CHARACTER SIZE	4.0mm/5.0mm/5.5mm*2		
		KIND OF CHARACTERS	<u> 6</u> 9 ⊕ ⊕ ÷ + (underscore) preinstalled		
NUMBERING FUNCTION		CTION	Automatic 4-digit decimal & hexadecimal numbering possible per text in ascending & descending order.		
DATA DISPLA	Y		LCD with white backlight (40 digits x 4 lines)		
INTERFACE			USB		
DATA STORAGE			Max. 1,000 lines in main memory & Max 1,000 lines/bank x 8 banks in extended memory		
PRODUCTION CAPACITY		PACITY	About 4,900 pcs. per hour (under TUBE mode, 5 digis x 1 line marking on 20mm-long tubes)		
POWER SOURCE			110 - 240VAC, 50/60Hz		
DIMENSIONS			432(W) x 280(D) x 302(H) mm		
WEIGHT			12.0 kgs		

\*1 Kinds of characters included may change depending on the character size & orientation.

\*2 3 different sizes of characters are included in one font area.

#### SOFTWARE (CTKPCMS for Windows for SP8600)

	Operating system (OS)	Windows 8/8.1/10/11	
Required specs for PC	Hardware	PC having features recommended by each OS and equipped with USB port.	
	RAM	Min. capacity recommended by each OS or above.	
	Hard disc drive	Min. capacity recommended by each OS or above.	
	Symbology	Compatible with Code 39	
	Character size	40 points and larger recommended	
Barcode marking functions	Check digits	Modulo 43 check digits can be appended.	
	Recommended applications	PVC tubes of 0.D. 4.0mm & larger (for marking barcodes only), Marker Labels & Marker Plates.	

#### PRECAUTIONS TO ENSURE SAFETY

## Before using the machine, be sure to read the instruction manuals and understand the proper usage of the machine.

"Windows" is a trademark of Microsoft Corporation. Actual color of the products may look slightly different to the photographs in this leaflet The information contained in this leaflet, specifications and external appearance of products are subject to change without notice.



#### MANUFACTURER CTK CORPORATION

4F, 2-28-14, Minami-Ikebukuro, Toshima-ku, Tokyo 171-0022 Japan Te I: +81-3-5953-9883 Fax: +81-3-5953-9884 https://en.hotmarker.com/

#### CONSUMABLES

#### Marking Foils

Ref.	Width (mm)	Length (M)	Color	Applications		
S611-20	20	200	Black	PVC tubes		
S625-20	20	200	White	Marker Labels Terminal ID boards		
S619-20	20	200	Black	Polyolefin heat shrink tubes		
S629-20	20	100	White			

#### Marker Labels (RoHS-compliant adhesive labels)

Size of	PVC	PET ("est" brand)	
each label (mm)	White	White	Silver
6 x 17	PVCW0617	PETW0617	PETS0617
6 x 20	PVCW0620	PETW0620	PETS0620
6 x 23	PVCW0623	PETW0623	PETS0623
6 x long type	PVCW0699	PETW0699	PETS0699

#### Marker Plates (Terminal ID boards)

High quality & smooth surface for best printing results. Packed in dust-protective transparent jacket.

Ref.	Width (mm)	Length (M)	Color
MP-80-25	8.0	25	White
MP-85-25	8.5	25	White
MP-95-25	9.5	25	White
MP-100-25	10.0	25	White

#### PVC tubes

Hotmarker brand of genuine PVC tubes. Most suitable to obtain legible printings with Hotmarkers.

#### **OPTIONAL PARTS**

The following accessories are available at extra cost.

USB English keyboard For stand-alone operation

Tube holder TH400

Space-saving tube holder for constant supply of tube

- Tube holder C-3 Floor-type tube holder
- Tube reel set For using different sizes of tubes with C-3 / TH400

Printed in Japan 20Y22